



# Information Redundancy as an Information Theoretic Criterion for Onset Detection

G. Van Dijck, M. M. Van Hulle,

Computational Neuroscience Research Group, Laboratorium voor Neuro- en Psychofysiologie, K.U. Leuven, Herestraat 49, B- 3000 Leuven.

## Abstract

We propose a criterion, called ‘maximal redundancy’, for onset detection in time series. The concept redundancy is inspired from information theory and indicates how well a signal locally can be explained by an underlying model exploiting past observations. It is shown that a local maximum in the redundancy is a good indicator for an onset. It is proven that ‘maximal redundancy’ detection is a statistical asymptotically optimal detector for AR processes. Moreover, the detector accounts for non-Gaussianity of the innovations in the AR processes, using negentropy. Several applications are shown where the new criterion has been successfully applied.

## Introduction

Previous research often started from the assumption that an onset is characterized by a change in the variance profile of a signal (see [1] for an overview). This assumption was made either heuristically (see the Hodges and Bui, Bonato et al., Lidierth, Abbink et al. references in [1]) or explicitly by means of a statistical model (*EstOpt*, *AGLRstep* and *AGLRramp* in [1]).

Here, we assume that the onset of a ‘signal of interest’ can be determined as a change in the information redundancy profile. In fact, it was shown ([2]) that the proposed *MaxRed* criterion is not contradictory to *EstOpt*, but rather is complementary to it. Both *EstOpt* and *MaxRed* are based on a log-likelihood ratio; however *EstOpt* assumes identical and independently distributed (i.i.d.) Gaussian variables whereas our *MaxRed* can handle dependent and non-Gaussian variables, by establishing the link with information theoretic concepts.

## Information Theoretic Equivalent for Onset Detection

Given 2 hypotheses  $H_1$  and  $H_0$ , the optimal statistical decision is determined by the Neyman-Pearson criterion [3]:

$$\ln \frac{p(y_j, y_{j+1}, \dots, y_k | H_1)}{p(y_j, y_{j+1}, \dots, y_k | H_0)} \underset{H_0}{\overset{H_1}{>}} \gamma \quad (1)$$

We then assume  $H_1$  is a model, where the current observation is a function of past observations, while  $H_0$  contains i.i.d. observations:

$$\begin{aligned} y_n &= f(y_{n-1}, y_{n-2}, \dots, y_{n-p}) + \varepsilon_n \\ H_0 : p &= 0 \\ H_1 : p &> 0 \end{aligned} \quad (2)$$

Note that the model in (2) contains the autoregressive model (AR) as a special case. We can further prove, by transforming the  $y_i$  into the  $\varepsilon_i$  variables, and making use of causality, that (2) is equivalent to (see [2]):

$$\sum_{i=j}^k (\ln p(\varepsilon_i) - \ln p(y_i)) \underset{k-j+1 \text{ large}}{\approx} (k-j+1)(-H(\varepsilon) + H(y)) \quad (3)$$

In (3), we used the *Shannon-McMillan-Breiman* theorem (see [4]) to establish the asymptotic result, where  $H(\cdot)$  is the Shannon entropy. It can be proven further [2], that (3) is equivalent to the *marginal information redundancy* [5]. Hence, we can state (1) combined with (2) intuitively as:

**“We choose in favour of  $H_1$  if there is a significant decrease in the number of bits needed to encode a sequence of observations, when we take into account the past observations”.**

## Applications

We show 2 applications, where the ‘maximal redundancy’ criterion has been successfully applied as an onset detection criterion.




Figure 1. Burst onset detection. The oscillating burst (in cyan) is an example of an acoustic event due to pitting. Detection of the burst occurs by detecting a minimum in the inverse redundancy profiles on top of the figure. The noisy signal was created from the burst signal by adding WGN until -14 dB SNR.




Figure 2. Voltage jumps onset detection. The electrochemical noise signal is shown on the bottom. The jumps are related to stress corrosion cracking (SCC) events. On top 2 exponential inverse redundancy profiles corresponding with 2 different parameter settings are shown. Note that at the onset of the jumps, about 110 s and 190 s, 2 distinctive minima (or maxima in redundancy) are obtained.

## References

- [1] G. Staude, C. Flachenecker, M. Daumer, and W. Wolf, “Onset Detection in Surface Electromyographic Signals: A Systematic Comparison of Methods”, *EURASIP Journal on Applied Signal Processing*, Hindawi Publishing Corporation, 2001:2, pp. 67-81.
- [2] G. Van Dijck, M. M. Van Hulle, “Onset Detection through Maximal Redundancy Detection”, *ICPR 2006*, oral presentation (15% acceptance rate).
- [3] S. M. Kay, *Fundamentals of Statistical Signal Processing: Detection Theory*, Prentice-Hall, 1998.
- [4] Shannon, C. E. (1948). “A Mathematical Theory of Communication”, *The Bell System Technical Journal*, 623-656.
- [5] S. Dubnov, “Generalization of Spectral Flatness Measure for Non-Gaussian Linear Processes”, *IEEE Signal Processing Letters*, August 2004, pp. 698-701.